Remote Cargo Hook Test Form
C3

DART AEROSPACE

Work Order _____   Customer _____

Serial Number _____   Date _____

# of Releases	Load (Lbs.)	Release Method	Remarks	Result	Pass/Fail
1	7,500	Static Hold	Hold for two Minutes and reduce load to zero	N/A	
10	1,500	Electircal, 25 volts	No "hang ups" permitted	N/A	
2	3,000	Electircal, 22 volts	Current shall not exceed 14.8A	Am	
2	2,500	Electircal, 22 volts	Current shall not exceed 14.8A	Am	
2	2,000	Electircal, 22 volts	Current shall not exceed 14.8A	Am	
2	1,500	Electircal, 22 volts	Current shall not exceed 14.8A	Am	
2	500	Electircal, 22 volts	Current shall not exceed 14.8A	Am	
1	3,000	Electircal, 20 volts	Current shall not exceed 14.8A	Am	
1	3,000	Electircal, 28 volts	Current shall not exceed 14.8A	Am	
1	3,000	Manual		N/A	
1	3,000	Impact Test	Impact shackle 10 times, shall not release	N/A	
1	N/A	Solenoid Ohms	Shall not exceed 1.8-2.3 Ohms	Ohm	
1	N/A	Electircal Continuity	Across both wires	N/A	

Test Conducted By: _____   Signature: _____